


10/521419
Rec'd PCT/TO 28 DEC 2004

PCT/SE 03 / 0 0 6 0 2

PRV

PATENT- OCH REGISTRERINGSVERKET
Patentavdelningen



Intyg Certificate

Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.

This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.



(71) Sökande Scania CV AB (publ), Södertälje SE
Applicant (s)

(21) Patentansökningsnummer 0202005-5
Patent application number

(86) Ingivningsdatum 2002-06-28
Date of filing

Stockholm, 2003-07-02

För Patent- och registreringsverket
For the Patent- and Registration Office

Sonia André
Sonia André

Avgift
Fee

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

PATENT- OCH
REGISTRERINGSVERKET
SWEDEN

Postadress/Adress
Box 5055
S-102 42 STOCKHOLM

Telefon/Phone
+46 8 782 25 00
Vx 08-782 25 00

Telex
17978
PATOREG S

Telefax
+46 8 666 02 86
08-666 02 86

A method for an engine

Technical Field of the Invention

5 The present invention relates to a method for identifying a fault associated with an individual cylinder of a multicylinder combustion engine. The method also relates to a computer program, a computer program product and a computer for identifying a fault associated with the individual cylinder.

10 Description of Related Art

When a multicylinder combustion engine fails to deliver its rated power, the problem may arise from the weakness or malfunctioning of one or two cylinders out of a total of, for example, eight cylinders. In the case of a diesel engine, malfunctioning of a
15 cylinder may be due to underfueling caused by failure of the fuel injector or to worn piston rings and valves which cause loss of compression. In case of a spark-ignition type engine, the malfunctioning of a cylinder may also be due to a faulty spark plug. Evidence of a malfunction may be roughness of engine operation, poor cylinder compression or reduced engine torque.

20

Today there exist a number of methods known to a person skilled in the art of identifying a weak or defective cylinder. In a common method for measuring the output torque from an individual cylinder in an internal combustion engine, the fuel supply to the cylinder to be tested is interrupted, whereas the other cylinders receive a
25 predetermined quantity of fuel. The speed of the engine (in rpm) is monitored during an acceleration of the engine and the time it takes for the speed to increase from a starting speed to a higher speed is counted. A relatively long acceleration time implies that the cylinder delivers a relatively high torque. The cylinders are thereby not tested one at a time. If there is something wrong with two or more fuel injectors/cylinders, it
30 becomes very difficult to determine which ones and the accuracy of the measured torque compared to the actual torque is deteriorated since the measured torque

originates from several cylinders. Therefore such methods require several other tests in order to relate a fault to a specific cylinder.

DE-19540826-A1 discloses a method for identifying individual cylinder faults. First, a specified operating condition of an IC engine is set and the rpm of the engine is determined. Then the fuel supply to the cylinder under test is interrupted. The rpm is redetermined. After that, it is determined whether the difference of the rpm before the fuel interruption minus the rpm after the fuel interruption is smaller than a predetermined limit value. If the answer is yes, a faulty function data related to this cylinder is produced. Also this method suffers from several disadvantages. One disadvantage is that the fuel injected to the cylinders has to be relatively low in order to stop the engine from racing. The interruption of fuel to only one cylinder is not enough to stop the engine from racing if the other cylinders receive a large quantity of fuel. However, there normally is a desire to test the engine when both running at a speed and having a supply of fuel according to typical driving situations for a vehicle, i.e. at a speed where the engine would race if this method is applied. Another disadvantage is that the difference between the rpm before and after the fuel interruption is relatively small for an engine with several cylinders. This makes it more difficult to read the difference and guess the character of a fault than if the difference was larger. One or more of the cylinders or fuel injectors to which fuel is supplied during the retardation that follows after the fuel interruption to the cylinder under test may be malfunctioning or they may have a reduced capacity and therefore introduce substantial variations during a whole or a part of a revolution. This also makes it more difficult to interpret the difference.

Summary of the invention

An object of the invention is to provide a reliable and accurate method for testing individual cylinders, which method makes it easy to discover problems associated with an individual cylinder.

The invention relates to a method for identifying a fault associated with an individual cylinder of a multicylinder combustion engine. The method comprises the steps of:

accelerating the combustion engine to a first engine speed;

interrupting the fuel supply to all cylinders except the individual cylinder, which

5 receives a predetermined amount of fuel supply, when the first engine speed is reached; and

counting the time it takes for the speed of the combustion engine to decrease from

either the first engine speed or a second engine speed, which is lower than the first engine speed, down to a third engine speed, which is lower than the second speed.

10 Hereby is achieved that fuel only is supplied to the individual cylinder during the counting step of the method. Moreover, it is achieved that an individual cylinder may be tested during an engine speed corresponding to typical driving/cruising speeds of a vehicle and that the amount of fuel injected into the cylinder also corresponds to a typical driving situation. Engine speed is throughout the description and the claims
15 defined as the commonly measured rotation speed of the engine in rpm or any corresponding parameter originated from the rotation speed of the engine.

Furthermore, a counted deceleration time is achieved, which may be used in calculations or comparisons with reference values in order to easily discover and identify a fault associated with the individual cylinder.

20

In one embodiment, the method comprises the further step of supplying a substantially equal first amount of fuel to all cylinders during the step of accelerating the combustion engine. Hereby a fast acceleration and an evenly distributed work load between all the cylinders are achieved.

25

In another embodiment, the method comprises the step of interrupting the fuel supply to the individual cylinder after the third engine speed has been reached. Hereby is achieved that no fuel is wasted during a further deceleration of the engine speed.

Furthermore, the deceleration is faster, which provides for a quicker method.

30

In yet another embodiment, the method comprises the step of keeping the speed of the combustion engine at a substantially constant low speed, which is lower than the third engine speed, before the method is repeated for testing the individual cylinder again or another of the cylinders of the combustion engine. Hereby an initial state for the engine can be achieved, in which state e.g. the rpm, fuel supply and charge air pressure are known. This makes the method even more reliable, since the method preferably always is started from the initial state and it is thereby easy to repeat the test with comparable test results.

10 In still another embodiment, the method comprises the step of comparing the counted time with a predetermined time representing a deceleration time for a well-functioning cylinder. Hereby an easy and fast way of identifying that there is a problem with an individual cylinder is achieved.

15 Suitably the combustion engine is a diesel engine in a vehicle, such as a truck.

The invention also relates to a computer program for identifying a fault associated with an individual cylinder of a multicylinder combustion engine, comprising computer readable program code means, which when run on a computer, such as an engine control unit or a computer connected to the engine control unit, causes an engine control unit to cause an acceleration of the combustion engine to a first engine speed;

computer readable program code means for causing the engine control unit to interrupt the fuel supply to all cylinders except the individual cylinder, which receives a predetermined amount of fuel supply, when the first engine speed is reached; and computer readable program code means for causing either the engine control unit or another computer connected to the engine control unit to count the time it takes for the speed of the combustion engine to decrease from either the first engine speed or a second engine speed, which is lower than the first engine speed, down to a third engine speed.

30

The computer program may comprise computer readable program code means for causing the engine control unit or another computer connected to the engine control unit to display a graphical user interface on a display. Hereby the advantages with a graphical user interface can be utilised for starting the method and displaying results from the method.

The computer program may comprise computer readable program code means for causing the engine control unit or another computer connected to the engine control unit to check whether all of at least one criterion for testing the individual cylinder is fulfilled. Hereby is achieved that the computer program may prevent the method from starting or interrupting the method at any time, if the at least one criterion is not fulfilled. This gives a safer testing, and helps to prevent accidents.

The computer program may also comprise computer readable program code means for causing the engine control unit or another computer connected to the engine control unit to compare a stored predetermined time with the time it takes for the speed of the combustion engine to decrease from either the first engine speed or the second engine speed to the third engine speed.

Furthermore the invention relates to a computer program product, such as a floppy disc, CD, DVD, flash memory, harddisk etc., comprising the computer program and a computer readable medium on which the computer program is stored. Hereby is achieved that the computer program easily can be loaded into and processed by computers.

25

Moreover, the invention relates to a computer, such as an embedded electronic engine control unit or a vehicle external computer comprising a storing means and a computer program according to claim 7 stored in the storing means. Hereby is achieved that an internal computer, such as an electronic engine control unit in a vehicle, as well as external computers connected to the engine control unit, are able to control the method according to the invention.

30

Brief Description of the Drawings

The objects, advantages and effects as well as features of the present invention will be more readily understood from the following detailed description of an example of a method, control unit, computer and computer program, as well as other embodiments, when read together with the accompanying drawings, in which:

Fig. 1 shows a schematic block diagram of a system for performing a method according to the invention,

Fig. 2 shows an engine control unit according to the invention,

Fig. 3 shows a block diagram of a method according to the invention,

Fig. 4 schematically shows a graph of the engine speed over a testing period, and

Fig. 5 shows a block diagram of an embodiment of the method.

Detailed Description of Embodiments

While the invention covers various modifications and alternative constructions, some embodiments of the invention are shown in the drawings and will hereinafter be described in detail. However, it is to be understood that the specific description and drawings are not intended to limit the invention to the specific forms disclosed. On the contrary, it is intended that the scope of the claimed invention includes all modifications and alternative constructions thereof falling within the spirit and scope of the invention as expressed in the appended claims to the full range of their equivalents.

25

Fig. 1 shows a schematic block diagram of a system for performing a method according to the invention. A vehicle (not shown), such as a truck and a ship, comprises an internal combustion engine 1 in the form of a diesel engine, here comprising four cylinders 2a-2d. The number of cylinders is kept to four for illustration purposes only. It must be understood that the invention is applicable to any multicylinder combustion engine with any known number of cylinders. Moreover,

30

although the embodiment described here relates to a combustion engine arranged in a vehicle, a person skilled in the art appreciates that the invention also is applicable to combustion engines not arranged in a vehicle; the combustion engine may for example be installed in a power plant. The combustion engine 1 is controlled by an electronic engine control unit 3 embedded in the vehicle. The engine control unit 3 is adapted to receive sensed engine data in the form of e.g. a toothed flywheel signal (TF-signal) and a gear signal. The TF-signal is received on a first line 4 from an engine-speed sensor 5 which senses rotation of the engine's toothed flywheel 6. The engine-speed sensor 5 may be e.g. an inductive type sensor or a hall-effect sensor. Of course there may be more than one engine-speed sensor 5 and other positions for measuring the engine speed, such as measuring the rotation the combustion engine's 1 crankshaft (not shown). The engine control unit 3 is also adapted to send control signals through a set of second lines 7a-7d to a fuel injector unit (not shown) respectively, for the supply of fuel to each cylinder 2a-2d. The gear signal is a discrete signal received on a third line 8 from e.g. a discrete transmission sensor 9, which typically provides the gear signal when the transmission is in neutral. All this is known to a person skilled in the art and is therefore not described more in detail.

In this embodiment the engine control unit 3 is connected to a vehicle external computer 10, for example an external PC laptop, through which the method according to the invention is initiated. Although not shown in Fig. 1 the external computer 10 may of course be indirectly connected to the engine control unit 3 via one or more other embedded or external electronic control units, gateways and interfaces. The communication between the external computer 10 and the engine control unit 3 may of course also be partly or substantially wireless.

Fig. 2 schematically shows the engine control unit 3, which comprises a first CPU 11 connected to a first port 12a via a first bus 13a in order to receive the TF-signal from the engine-speed sensor 5, a second port 12b via a second bus 13b for receiving the gear signal from the transmission sensor 9, a third port 12c via a third bus 13c for communication with the injector units and a fourth port 12d via a fourth bus 13d for

communication with the external computer 10. The first CPU 11 is also connected to at least one storing means 14, such as a hard disk, a flash memory and a ROM (Read-only memory), via a fifth bus 13e. The engine control unit 3 suitably also comprises other components commonly used in an ECU (Electronic Control Unit) for vehicles, e.g. a Random-Access memory; an EEPROM, a Bus Controller and A/D-converters (not shown) in the case where e.g. both the gear signal and TF-signal are analogue signals. Installed in the storing means 14 are e.g. an engine speed sensor interface computer program 15 for interpreting the TF-signal, a transmission sensor interface computer program 16 for interpreting the gear signal, a fuel control computer program 17 for controlling the supply of fuel to the cylinders 2a-d and a first communication interface computer program 18 for communication with the external computer 10. These computer programs 15-18 may be program modules in an engine control computer program. It must also be understood that several functions may be implemented as partly software and hardware as known to a person skilled in the art.

Fig. 3 schematically shows an example of the external computer 10, which comprises a second CPU 19 connected to a fifth port 12e via a sixth bus 13f for communication with the engine control unit 3 and a sixth port 12f via a seventh bus 13g for communication with a display, which may show a graphical or character-based user interface. The second CPU 19 is also connected to at least one second storing means 20, such as a hard disk, a flash memory and a ROM via an eighth bus 13h. The second storing means 20 comprises a cylinder test computer program, which suitably comprises a second communication interface program module 21 for communication with the engine control unit 3, a user interface program module 22 and a criteria checking program module 23. The cylinder test computer program may be downloaded to the external computer, e.g. directly from a computer program product 24, such as a floppy disk (see Fig. 1), an external hard disk, a CD, a DVD and a flash memory, and through a server via a Local Area Network or Wide Area Network. Although not shown in any figures as alternative embodiments, it must be understood that the invention also comprises embodiments where at least a part of the cylinder test computer program may be installed as separate computer programs in the engine

control unit and/or another ECU in the vehicle in order to e.g. create redundancy or a distributed cylinder test computer program.

An embodiment of the method according to the invention will now be described in conjunction with Fig. 4 and Fig. 5. As an initial first step S1, a person starts the cylinder test computer program on the external computer 10, which causes a display 25 (see Fig. 1) connected to the external computer 10 to show e.g. a GUI (graphical user interface). In a second step S2, the person requests a start of the cylinder test by e.g. pushing a start button in the GUI. The request is sent to the engine control unit 3, which in a third step S3 checks whether all of at least one criterion for starting the cylinder test is fulfilled. The criterion may be that the gear signal is received from the transmission sensor 9, i.e. that the gearbox is in the neutral position. Another criterion may be that the parking brake (not shown) of the vehicle is activated. Yet another criterion is that the sensed vehicle speed is zero or below a certain value. Still another criterion may be that a pedal position sensor (not shown) indicates that e.g. the clutch pedal is unaffected. If the at least one criterion is not fulfilled, the request to start the testing will be denied and step S2 has to be carried out again. When the at least one criterion is fulfilled the cylinder test is started and the method continues with a fourth step S4 in which the cylinder test computer program causes the external computer 10 to instruct the engine control unit 3 to start the combustion engine 1. When the combustion engine 1 has been started and is running at a relatively low speed L0, e.g. idle speed, a fifth step S5 starts, in which the cylinder test computer program causes an acceleration of the combustion engine up to a first engine speed L1. All the cylinders 2a-2d could throughout this acceleration be supplied with an equal amount of fuel. The first engine speed L1 preferably corresponds to a speed level above typical propulsion conditions of the vehicle. When the first engine speed L1 is reached, the fuel supply to all cylinders except the cylinder to be tested is interrupted. This is done in a sixth step S6, which correspond to the time t_0 in Fig 4. The fuel supply to only the tested cylinder is not enough to keep the first engine speed L1, since the braking effect caused by e.g. internal compression strokes in the other cylinders is more powerful than the power output from the tested cylinder when the engine is running at the first engine speed L1.

Therefore the interruption in step S6 causes the speed of the engine to decrease. The fuel supply to the tested cylinder may even be increased without overcoming the braking effect. Thus the fuel injection for each cylinder up to L1 may be kept relatively low compared to the fuel injection for the tested cylinder after the fuel interruption to the other cylinders. At the same time as the fuel supply is interrupted, i.e. at time t_0 , the engine control unit 3 and/or the external computer 10 starts to count the time, while monitoring of the speed of the engine continues. This is performed in a seventh step S7. In an alternative seventh step S7 the counting starts when the speed of the engine has decreased to a second engine speed L2 after the interruption, which second speed L2 in this embodiment only is slightly lower than the first engine speed L1. The start of the counting in the alternative seventh step corresponds to time t_1 in Fig. 4, in which t_1 is soon after the interruption of the fuel supply in order to still be able to test an individual cylinder working at a relatively high engine speed. As soon as the speed of the engine has decreased to a predetermined third speed L3, the counting stops. The stopping is executed in an eighth step S8, which corresponds to time t_2 in Fig. 4. The time between t_0 and t_2 , or in the alternative step S7, t_1 and t_2 , is then used for, e.g., a direct comparison with a deceleration time for a healthy cylinder. The deceleration time for the healthy cylinder may for instance be stored in a database in the external computer 10, suitably as a part of the cylinder test computer program. If the measured time between t_0 and t_2 and t_1 and t_2 respectively, deviates more from the deceleration time for the healthy cylinder than to a predetermined extent, a conclusion can be drawn that there is a fault associated with the tested cylinder.

In a ninth step S9 in this embodiment, an equal amount of fuel is supplied again to all the cylinders after the third engine speed has been reached and the counting has stopped. The start of the fuel supply corresponds to the time t_3 in Fig. 4. However, this time the fuel supply is much lower than during the acceleration in step S5, and the speed of the engine continues to decrease, but in a more controlled way, down to the low speed L0, where, if needed, more fuel is supplied in order to keep the low speed L0 when reached. The low speed L0 is controlled during a tenth step S10. In an alternative step S9, the fuel supply to the tested cylinder is interrupted after the

- counting has stopped. The interruption in the alternative step S9, may be performed with the help of the ordinary engine control computer program, which may order the engine to return to idle speed. Typical modern engine control computer programs causes an immediate interruption of the fuel supply if a current speed is higher than a requested speed. The alternative step S9 saves fuel and causes a faster return to the low speed L0. Fuel is again supplied to all the cylinders 2a-2d first when the speed of the engine has reached down to or is close to the low speed L0 in order to maintain the low speed L0 before the steps S5-S10 are repeated.
- 10 The steps S5-S10 may be repeated several times for testing one of the cylinders several times in order to get a mean time value which statistically is more accurate than a single performance of the steps S5-S10. The steps S5-S10 may also be repeated for all the cylinders, i.e. another cylinder may be tested in a subsequent repetition of step S5-S10 directly following a previous performance of step S5-S10 in which another
- 15 cylinder was tested. The checking of the at least one criterion suitably continues as long as one of the steps S4-S10 is performed. If, for example, the gear signal ceases from the transmission sensor 9, the testing and the fuel supply to the combustion engine 1 are immediately interrupted.

11
12
13
14
15
16
17
18
19
20

Claims

1. A method for identifying a fault associated with an individual cylinder of a multicylinder combustion engine (1),
5 comprising the steps of:
accelerating the combustion engine (1) to a first engine speed (L1);
interrupting the fuel supply to all cylinders except the individual cylinder, which receives a predetermined amount of fuel supply, when the first engine speed (L1) is reached; and
10 counting the time it takes for the speed of the combustion engine (1) to decrease from either the first engine speed (L1) or a second engine speed (L2), which is lower than the first engine speed (L1), down to a third engine speed (L3).
2. A method according to claim 1, comprising the step of supplying a substantially
15 equal first amount of fuel to all cylinders (2a-2d) during the step of accelerating the combustion engine (1).
3. A method according to claim 1 or 2, which after the third engine speed (L3) has been reached comprises the step of interrupting the fuel supply to the individual
20 cylinder.
4. A method according to any one of claims 1-3, comprising the step of keeping the speed of the combustion engine (1) at a substantially constant low speed (L0), which is lower than the third engine speed (L3), before the method is repeated for testing the
25 individual cylinder again or another of the cylinders (2a-2d) of the combustion engine (1).
5. A method according to any one of the preceding claims, comprising the step of comparing the counted time with a predetermined time representing a deceleration
30 time for a well-functioning cylinder.

6. A method according to any one of the preceding claims, wherein the combustion engine (1) is a diesel engine in a vehicle.

7. A computer program for identifying a fault associated with an individual cylinder of a multicylinder combustion engine (1), comprising computer readable program code means for causing an engine control unit (3) to cause an acceleration of the combustion engine (1) to a first engine speed (L1);
computer readable program code means for causing the engine control unit (3) to interrupt the fuel supply to all cylinders except the individual cylinder, which receives a predetermined amount of fuel supply, when the first engine speed (L1) is reached;
and
computer readable program code means for causing either the engine control unit (3) or another computer (10) connected to the engine control unit (3) to count the time it takes for the speed of the combustion engine (1) to decrease from either the first engine speed (L1) or a second engine speed (L2), which is lower than the first engine speed (L1), down to a third engine speed (L3).

8. A computer program according to claim 7, comprising computer readable program code means for causing the engine control unit (3) or another computer (10) connected to the engine control unit (3) to display a graphical user interface on a display (25).

9. A computer program according to claim 7 or 8, comprising computer readable program code means for causing the engine control unit (3) or another computer (10) connected to the engine control unit (3) to check whether all of at least one criterion for testing the individual cylinder is fulfilled.

10. A computer program according to anyone of claims 7-9, comprising computer readable program code means for causing the engine control unit (3) or another computer (10) connected to the engine control unit (3) to compare a stored predetermined time with the time it takes for the speed of the combustion engine (1) to

decrease from either the first engine speed (L1) or the second engine speed (L2) to the third engine speed (L3).

11. A computer program product (24) comprising a computer program according to
5 claim 7 and a computer readable medium on which the computer program is stored.

12. A computer, such as an embedded electronic engine control unit (3) or a vehicle external computer (10) comprising a storing means (14, 20) and a computer program according to claim 7 stored in the storing means (14, 20).

Abstract

The invention relates to a method for identifying a fault associated with an individual cylinder of a multicylinder combustion engine (1), comprising the steps of:

- 5 accelerating the combustion engine (1) to a first engine speed (L1);
- interrupting the fuel supply to all cylinders except the individual cylinder, which receives a predetermined amount of fuel supply, when the first engine speed is reached; and
- counting the time it takes for the speed of the combustion engine to decrease from
- 10 either the first engine speed or a second engine speed (L2), which is lower than the first engine speed, down to a third engine speed (L3).

The invention also relates to a computer (3, 10), a computer program and a computer program product (24).

15 (Fig. 5)

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178

1/3

Fig. 1





Fig. 2



2/3

Fig. 3





Fig. 4



3/3

Fig. 5

